

FIFR PLUNGE BARREL

Usage & Care Instructions

Setting Up in Cold Weather

- If you're using the barrel in a cold environment, soak it in warm water for 2-3 minutes before use.
- This helps the material become more flexible.

Cleaning the Barrel

- Use warm water only to clean the barrel.
- Do not use detergents or cleaning agents, as they may damage the material.

Filling the Barrel

- Use water with a temperature no higher than 50°C (122°F).
- Fill the barrel to your desired level, but do not exceed two-thirds of its total height.

Before First-Time Use

- A slight plastic smell may be noticeable at first, this is normal and will fade over time.
- The tub is made from safe, non-toxic materials and is completely safe to use.

Extreme Temperature Guidelines

In Extreme Cold (below -40°C / -40°F):

- Drain all water from the barrel.
- Store the barrel **indoors** to prevent material damage from freezing water.




In Extreme Heat (above 40°C / 104°F):

- Avoid leaving the barrel in **direct sunlight** for long periods.
- UV rays can cause the material to **weaken or degrade** over time.



STEP
01



Open up the package and lay the deflated barrel on a flat surface

STEP
02



Pop the air inlet / outlet up

STEP
03



Insert the air pump nozzle and inflate the barrel

STEP
04



Your barrel is now set up

STEP
05



To deflate, press the air inlet / outlet down & allow air to escape

STEP
06



Fold the deflated barrel and store in the bag cover

WARNING!

ONLY PUMP THE BARREL TO A PRESSURE OF 4-6 PSI. ANY MORE THAN THIS MAY CAUSE DAMAGE TO THE BARREL.